



569.00 EUR

incl. 19% VAT, plus [shipping](#)

- wlan !



- Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor
- Intel® Coffee Lake-S H310 Chip
- Support Dual Channel DDR4 2133MHz up to 32GB
- 1* Intel® I219-V Giga LAN + 1* Intel® i255V 2.5Gb LAN
- Support 1* SATA III (6Gb/s) & M.2 (M key 2242)
- 1* M.2 E key Support CNVi
- 4* RS232 (COM1/2 Support 5V/12V TTL, 4* USB3.0
- Support HDMI/VGA /EDP (Option)
- DC 12~24V Input

Model	- HBJC501C8HV-H310 - HBJC501C8HVI-H310 (Wifi)
CPU/Chipset	- Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor (TDP 35W) - Intel® Coffee Lake-S H310 Chip
BIOS	- AMI 128MB SMT Flash ROM
Memory	- 2* DDR4 2133MHz up to 32GB
Network	- 1* Intel® I219-V GbE - 1* Intel® I225-V 2.5GbE - 1* WIFI2.4/5G + BT4.1 (M.2 E key)
Graphics	- 1* HDMI (Max. Resolution : 4096x2160@30Hz) - 1* VGA (Max. Resolution: 1920x1080@60Hz) - 1* eDP (Option, Max. Resolution: 4096x2304@60Hz) - Support Dual Displays or Triple Displays with eDP
Storage	- 1* 2.5" SATA 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm) - 1* M.2 (M-key 2242)
Expansion slot	- 1* PCIe x4 slot - 1* WIFI2.4/5G + BT4.1 (M.2 E key)
Rear Panel I/O	- 4* USB3.0 - 1* HDMI - 1* VGA - 1* eDP - 2* RJ45 - 4* RS232 - 1* Line-out +MIC - 1* DC Jack - 1* Power Button

Front Panel I/O	- NA
Internal Connector	- NA
Compliance	- CE, FCC, RoHS, ErP Ready (option)
Power Source	- MB: DC 12~24V input - Adapter: AC_90~240V/ DC_19V / 120W
Temperature	- Operating Temperature: -10 ~ 50° C - Storage Temperature: -20 ~ 60° C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
Dimensions	- System: 264 (W) x 199.4 (D) x 58 (H) mm
OS Support	- Windows 10, Linux