



439.00 EUR incl. 19% VAT, plus shipping

- 4Kp30 !
- HDMI !
- M.2 !

Support: <u> Datasheet</u>

The Latest M.2 Compact Form Factor with 4K 30fps Resolution Nowadays, the M.2 compact form factor has become the hot trend. The dimension of a PCI Express M.2 is extremely compact and designed perfectly to fit into small-footprint embedded systems for industrial applications. Conforming to the most popular standard of M.2, CN311-H is the ideal solution for the education sector and industrial PCs, it features PCIe Gen2 x2 interface with a theoretical bandwidth of 8 Gb/s.

Compatible with HDMI 1.4a standards, CN311-H enables single channel 4096x2160 resolution at 30fps loss-less video data throughput, capable of either capturing or recording at 4096x2160 @ 30fps.

I/O Board Design with HDMI Micro Coaxial Cable Unlike most of M.2 capture cards, AVerMedia makes a breakthrough in the I/O board design. Connected via an HDMI micro coaxial cable, CN311-H can convey 4K video data efficiently, steadily and also benefit the configuration of embedded systems

- Max. input resolution 4096x2160 30fps
- Max. capturing/ recording 4096x2160 30fps
- The latest M.2 compact interface
- I/O Board design with HDMI micro coaxial cable
- Hardware video processing:
 - 1. Hardware scaling
 - 2. De-interlacing
 - 3. Color space conversion
- · Ideal for industrial, medical, education and enterprise applications

Host Interface Audio Format Audio Sampling Rate Connector Type Input Interface

Video Format

Color Depth Channel No. Max. Input Resolution Max. Recording Resolution PCIe Gen2 x 2 HDMI embedded audio 32/44.1/48KHz HDMI Type A HDMI 1.4a, DVI-D 1.0 YUV444: IYU2, AYUV, V410, Y410 YUV422: YUY2, YUYV, UYVY, V210, Y210 YUV420: I420, NV12, YV12 RGB: RGB565, RGB555, RGB24, RGB32, ARGB 8-bit/10-bit 1Ch 4096 x 2160 @ 30fps 4096 x 2160 @ 30fps



M.2

3.8 W 0°C ~ 40°C

22 x 80 mm

640x480p @ 59.94/60/72/75/85

720x480p @ 59.94/60

720x576p @ 50/100 800x600p @ 56/60/72/75/85/120 1024x768p @ 60/70/75/85/120 1152x864p @ 75 1280x720p @ 50/59.94/60/100/120 1280x768p @ 60/75/85/120 1280x800p @ 60/75/85/120 1280x960p @ 60/85 1280x1024p @ 60/75/85 1360x768p @ 60/120 1366x768p @ 60 1400x1050p @ 60/75/85 1440x900p @ 60/75/85 1600x1200p @ 60 1680x720p @ 24/25/30/50/60 1680x1050p @ 60 1920x1080i @ 50/59.94/60 1920x1080p @ 23.98/24/25/29.97/30/50/59.94/60/120 1920x1200p @ 60/75/85 2048x1152p @ 60 1792x1344p @ 60/75 1856x1392p @ 60/75 1920x1440p @ 60/75 2560x1080 @ 24/25/30/50/60 2560x1440 @ 60 2560x1600 @ 60RB 3840x2160 @ 24/25/30 4096x2160 @ 24/25/30 640x480 @ 59.94/60 720x480 @ 59.94/60 720x576 @ 50 1280x720 @ 50/59.94/60 1920x1080@ 23.98/24/25/29.97/30/50/59.94/60 **Bypass Mode** 1920x1200p @ 60/75/85 2048x1152p @ 60 1792x1344p @ 60/75 1856x1392p @ 60/75 1920x1440p @ 60/75 2560x1080 @ 24/25/30/50/60 2560x1440 @ 60 2560x1600 @ 60RB 3840x2160 @ 24/25/30 4096x2160 @ 24/25/30 Software encoding Yes Windows 7/ 8.1/ 10 (32/ 64 bit)* Linux (based on V4L2, support x86, x64)

Input Resolution

Output Resolution

Encoding Mode Multi-Card Support

Supported OS

Form Factor Dimension (L x W) Power Consumption Operating Temperature

Operating Humidity Storage Temperature Safety Certification

<u>CN311-H</u>

SDK kits

0% ~ 95% relative humidity -30°C ~ 80°C FCC / CE Ordering Information 4K 30FPS HDMI M.2 Capture Card I/O Board, HDMI Micro Coaxial Cable SDK Pro SDK Premium add-on kits