



249.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Alder Lake-S H610 !
- Half Hight !
- Mini ITX !

- Intel® 12/13th LGA1700 Socket Processor (Max. 65W TDP)
- Intel® Alder Lake-S H610 Chipset
- 2\* DDR4 3200MHz UDIMM up to 64GB
- 1\* HDMI, 1\* DP, 1\* LVDS or eDP
- 1\* GbE
- 2\* USB3.2 (Gen.2), 2\* USB3.2(Gen.1), 5\* USB2.0
- 1\* M.2 M-key, 2242/2280(PCI-Ex4), 1\* M.2 E-key, 2230, 2\* SATAIII (6Gb/s)
- Onboard TPM2.0 (Option)
- 19V DC-in

|                  |   |  |
|------------------|---|--|
| Model            | – LI25-H6100<br>– LI25-H6102 (TPM2.0)   |  |
| Form Factor      | – Mini-ITX (170 * 170mm)  |  |
| Processor System | – Intel® 12/13th LGA1700 Socket Core i9/i7/i5/i3/Pentium/Celeron Processor (Max. 65W TDP)<br>– Intel® Alder lake-S H610 chipset<br>– AMI Flash ROM BIOS |  |
| Memory           | – 2* DDR4 3200MHz Dual Channel SO-DIMM up to 64GB   |  |
| Storage          | – 2* SATAIII (6Gb/s)<br>– 1* M.2 M-key (2242/2280 PCI-Ex4 Gen.3 interface)  |  |
| Expansion        | – 1* M.2 E-key (2230, CNVi/PCI-Ex1/USB2.0, Support WIFI/BT Module)  |  |

|                |   |
|----------------|---|
| Ethernet       | – 1* REALTEK® RTL8111H 10/100/1000Mbps  |
| Graphics       | – Intel® HD Graphics, shared memory<br>– 1* EXT HDMI2.0 (Max Resolution: 4096x2160@60Hz)<br>– 1* EXT DP1.4 (Max Resolution: 7680x4320@60Hz)<br>– 1* INT LVDS (Max Resolution: 2560*1600@60Hz)<br>– 1* INT EDP1.2 (Max Resolution: 1920*1080@60Hz)<br>– Support Triple Displays  |
| Audio          | – HD audio: Realtek ALC897  |
| Watchdog Timer | – From Super I/O to drag RESETCON#<br>– 256 segments (10sec ~ 255min)   |
| Internal I/O   | – 2* USB3.2 (Gen.1)<br>– 3* USB2.0 (PH2.54)<br>– 1* 8bit GPIO (5V)<br>– 2* SATAIII (6Gb/s)<br>– 1* SATA Power<br>– 1* LVDS(or eDP) + 1* Inverter<br>– 1* 2pin Power connector<br>– 1* Chassis intrusion<br>– 1* FP_ Audio<br>– 1* 4pin Speaker header (for 3W Amplifier, PH2.0)<br>– 1* 4pin Speaker header (for Buzzer, PH2.54)<br>– 1* FP_JW<br>– 1* SMBUS + 1*AT model<br>– 1* CPU FAN Header (Smart FAN) + 1* SYSTEM FAN Header (W/O Smart FAN) |
| External I/O   | – 2* USB3.2 (Gen.2)<br>– 2* USB2.0<br>– 1* HDMI2.0<br>– 1* DP1.4<br>– 1* RJ45<br>– 1* Line-Out<br>– 1* MIC<br>– 1* DC Jack (19V DC in)  |
| Power          | 19V DC in, AT/ATX Supported<br>– AT: Directly PWR on as Power input ready<br>– ATX: Press Button to PWR on after Power input ready  |
| Compliance     | – CE, FCC, LVD, RoHS, REACH (Option)  |
| Temperature    | – Operating Temperature: 0 ~ 60° C (with 0.7m/s air flow)<br>– Storage Temperature: -20 ~ 70° C<br>– Humidity: 10% ~ 90% RH @40°C (non-condensing)  |
| OS Support     | – Windows 10 / 11, Linux  |