

649.00 EUR
incl. 19% VAT, plus [shipping](#)

- NVidia Nano 8G !



Support:  [Specifications](#)

AVerMedia Engineering Kit D131LON built with NVIDIA® Jetson Orin™ Nano module, which brings next-level AI performance and power-efficient capability for all autonomous machines. This efficient SoM makes advanced analytics possible while providing the ability to handle a host of other embedded IoT applications.

- Supports Super Mode for Jetson Orin™ Nano
- 1 x 2 Lane MIPI CSI-2 Camera input
- 1 x M.2. E key 2230 for Wi-Fi (AC9260)
- 1 x M.2. M key 2280 for SSD (not included)
- 1 x GbE RJ-45 (Option PoE), 40-pin expansion header
- 4 x USB 3.2 Gen 1 Type A (Total Bandwidth: 5Gbps)
- 1 x 4Kp30 HDMI output for Orin Nano
- Operating temperature: 0°C ~ 65°C
- Dimension: 113mm(W) x 101.4mm(L) x 57.8mm(H)/Weight: 220g
- Support 24/7 secure remote monitoring, control, and OTA deployment empowered by Allxon

Model

D131LON

NVIDIA Jetson SoM

Jetson Nano 8G

BSP

Applied to NVIDIA BSP directly*

Networking

1x GbE RJ-45 (PoE option)

1x M.2. key E 2230 for Wi-Fi (AC9260)

Display Output

1x HDMI 3840 x 2160 at 30Hz for Orin Nano

Operating temperature 0°C~65°C

Storage temperature -40°C ~ 85°C

Temperature

Relative humidity 40 °C @ 95%, Non-Condensing

MIPI Camera Inputs

1x 2 lane MIPI CSI-2, 15 pin FPC 1mm Pitch Connector

USB

1x USB 2.0 Micro-B for recovery

4 x USB 3.2 Gen 1 Type A (Total Bandwidth: 5Gbps)

Storage

1x M.2. key M 2280 for SSD

Expansion Header

40-pin: 1x UART, 2x SPI, 2x I2C, 1x I2S, 6x GPIOs

1x OOB supported by Allxon

DC 9~24V

DC IN Jack on board: 7A~2.6A

Power requirement

ATX 4pin: 7A~2.6A

Thermal Solution

Fan

Buttons

Power and Recovery

113mm(W) x 101.4 mm(L) x 57.8 mm(H)

Dimensions

Weight: 220g

Certifications

CE, FCC, KC, UKCA

Package

1 x Carrier Board

1 x NVIDIA® Jetson Orin Nano module + Fan

WIFI KIT

PSE Board

APPRO IMX179 Camera module

Optional

256G SSD

12V Power Adapter

Power Cord