



148.00 EUR

incl. 19% VAT, plus [shipping](#)

- VIA C7 NanoBGA CPU
- 1.5 Ghz !
- DDR-II !
- 12W

This board is based on the latest VIA C7 architecture.

7F2WE-1G5-OC Specifications	
Processor	VIA C7 1.5 GHz processor
Chipset	VIA CN700 north bridge
	VIA VT8237R south bridge
System Memory	1 DDR2 400/533 DIMM
	Up to 1GB memory size
VGA	Integrated VIA UniChrome AGP graphics
Expansion Slots	1 PCI
Onboard IDE	4 Ultra DMA 133
Onboard Serial ATA	2 SATA connectors
Onboard Floppy	1 Floppy Port
Onboard USB	8 USB 2.0
Onboard LAN	VIA 6103 10/100
Onboard Audio	ALC655 6 channel AC'97 codec
Onboard TV Out	VIA VT1622A TV encoder
Onboard 1394	IEEE 1394

<b>Back Panel I/O</b>	<p>1 1394</p> <p>1 RCA video</p> <p>1 VGA port</p> <p>2 USB 2.0</p> <p>1 LAN port</p> <p>2 IEEE 1394 ports</p> <p>1 serial ports</p> <p>1 PS2 mouse port</p> <p>1 PS2 keyboard port</p> <p>3 audio jacks: line-out, line-in, and mic-in</p>
<b>Onboard I/O Connectors</b>	<p>3 USB 2.0 connectors for 6 USB ports</p> <p>1 parallel port</p> <p>1 VGA port</p> <p>2 serial ports</p> <p>1 PS2 keyboard connector</p> <p>1 PS2 mouse connector</p> <p>1 floppy port</p> <p>Line-in/out/MIC audio ports</p>
<b>BIOS</b>	<p>Award BIOS LPC 4Mbit Flash memory</p>
<b>System Monitoring &amp; Management</b>	<p>CPU temperature</p> <p>Modem ring wake up</p> <p>RTC Alarm</p> <p>Keyboard power on</p> <p>System temperature</p> <p>System voltage</p> <p>Fan speed</p>
<b>Operating Humidity</b>	<p>0% - 95% (relative humidity; non-condensing)</p>
<b>Form Factor</b>	<p>Mini-ITX (17cm x 17cm)</p>
<b>Includes</b>	<p>ATA 133 flat cable (40 wire, 80 conductor, 3 connectors)</p> <p>CD</p> <p>SATA Cable</p> <p>Floppy Cable</p>