




149.95 EUR

incl. 19% VAT, plus [shipping](#)

- 2cm height !
- Mini-PCI Express !
- Hyper-Threading !
- 10-19VDC Input !

Support: [Cedar Trail Review \[DE\]](#) | [Cedar Trail Review \[EN\]](#) | [DN2800MT Review \[DE\]](#) | [DN2800MT Review \[EN\]](#)

- Successor model of Intel D945GSEJT mainboard
- Dual-core Atom with Hyper Threading
- Slim form factor; <20mm z-height
- Meets channel All-In-One specification
- ExpressCard/34 adapter option (mobile ecosystem compatibility) via PCIe mini Card
- Supports new Mobile SATA (SSD) card via full-length PCIe Mini Card
- Supports Z-U130 flash drive
- Wide-range (10-19V) input voltage tolerance
- High current rating (up to 1.3A) on two back-panel USB ports
- TPM stuffing option

Name	DN2800MT
Form Factor	Mini-ITX Mainboard
CPU	Intel® Atom™ N2800 (2x 1.86GHz) 1MB Cache, With Hyper-Threading
Chipset	Intel NM10 Express
Graphics	VGA + HDMI + LVDS + eDP
Memory	2x SO-DDR3 800/1066, 4GB max, Single channel
LAN	1x Intel 10/100/1000 MBit

Connectors (rear)	- 4x USB 2.0 (2x with High-Current 1.3A) - 1x LAN RJ-45 - 2x Audio - 1x HDMI - 1x VGA - 1x DC-In (10-19V)
Audio	2+2 Channel HD Audio
Connectors (internal)	- 2x SATA-II (3GB/s) - 4x USB 2.0 - 1x PCIe - 2x Mini-PCle - Front Audio - SPDIF - 1x LPT - 2x RS232 - LVDS (Dual 24bit) - eDP (4-lane 24bit) - Z-U130 Flash Drive support - TPM stuffing option - Mobile SATA (SSD) support via Mini-PCle - ExpressCard/34 support via Mini-PCle
Included	- DN2800MT Mainboard (with 2x 1.86Ghz Atom CPU) - I/O ATX rear plate - 1x SATA cable - Quickstart-Guide - Drivers CD

Note :

- If you do not get picture on DSUB-15 VGA, then press CTRL+ALT+F1