

FleetPC-8-i7C

Intel Gen6 Core i7-6600U CPU with 4 x GbE LAN On-Board Computer



Delay Time



Power Ignition



Wide Range



Wireless



Battery backup

Taiwan Patent No. M447854
Taiwan Patent No. M448011

System

CPU Intel Gen 6 Core i7-6600U 2.6GHz up to 3.4GHz
Intel Gen 6 Core i5-6300U 2.4GHz up to 3.0GHz
Intel Gen 6 Core i3-6100U 2.3GHz
Intel Gen 6 Dual Core 3955U 2.0GHz

Memory 2 x DDR4 2133 MHz SO-DIMM up to 32GB

Chipset Intel 6th Generation Core SoC Processor

LAN Chipset Intel I210-AT Gb/s Ethernet Controllers Onboard
Support PXE and WOL

Audio Realtek ALC662 HD Codec Onboard

Watchdog Watchdog Timer Support, Offer 1 – 255 Step

TPM 2.0

I/O

Serial Port 4 x RS-232 (2 with RS-422/485 (Auto Direction Control))

USB Port 2 x USB 3.0 Ports, 2 x USB 2.0 Ports

LAN 4 x RJ45 Ports for GbE (1 port with iAMT)

Video Port 1 x DVI-I*, 1 x VGA and 1 x DP
(support Triple Independent Display)

DIO Port 4 In and 4 Out

Audio 1 x Line-out and 1 x Mic-in (Line-in Optional)

SIM Card Socket 2 x SIM Card Sockets Supported Onboard with eject

Expansion Bus 3 x mini-PCIe cards, 1 x M.2 2230 A-E Key

* Use only with Single Link DVI Cables.

Graphics

Graphics Intel® HD Graphics 520
DirectX Video Acceleration (DXVA) for Accelerating Video Processing - Full AVC/VC1/MPEG2 HW Decode
Supports DirectX 11/10.1/10/9 and OpenGL 4.0

Resolution Max Resolution (HDMI1.4) : 4096x2304@24Hz
Max Resolution (DP) : 4096x2304@60Hz

Features

- Intel Core i7-6600U
- Wireless support LTE w/ Dual SIM Cards, WLAN, GPS Dead Reckoning, WiFi, BT (Optional)
- 9V - 48V DC Power Input
- Smarter Vehicle Power Ignition for Variety Vehicle
- Dual Hot Swappable SATA Storage, RAID 0,1,5
- 1 x CAN Bus 2.0B (Optional)

Storage

Type 2 x 2.5" Drive Bay for SATA Type HDD/SSD, RAID 0, 1, 5
1 x SATA DOM

Power Requirement

Power Input 9V - 48V DC Power Input

Power Protection Automatics Recovery Short Circuit Protection

Power Management Vehicle Power Ignition for Variety Vehicle

Power Off Control Power off Delay Time Setting by BIOS and Software

Battery (UPS) Internal Battery Kit for 10 Mins Operating (Optional)

Patent No. : M447854 - Build-in Battery

Environmental

Operating Temp. -40°C ~ 70°C

Storage Temp. -40°C ~ 85°C

Relative Humidity 0% RH – 95% RH

Vibration(random) IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis with SSD

Vibration Operating MIL-STD-810G, Method 514.6, Procedure I, Category 4

Shock Operating: MIL-STD-810G, Method 516.6, Procedure I,
Trucks and semi-trailers=15G (11ms) with SSD

Certifications CE, FCC Class A, E-13

Mechanical

Construction Aluminum Alloy

Mounting Supports Both of Wall-mount/VESA-mount

Weight 1980 g (Barebone)

Dimensions 250 x 150 x 55 mm

Ordering Information

Part Number FleetPC-8-i7C

Description Intel Gen6 Core i7-6600U CPU with 4 x GbE LAN
On-Board Computer

All specifications are subject to change without notice.